

DATASHEET

SPEED



GENERAL

Art.Nr:	TAC-0002	Standards:	EN 353-1:2014+A1:2017
GTIN:	4030281122296	Net weight:	1.06 kg
E-class number:	40-02-01-90	Gross weight:	1.35 kg
Customs tariff number:	84798997		

DATASHEET

SPEED

The innovative SPEED climbing protection runner is the world's only runner with two redundant catch systems and speed-dependent catch function. The catching bar is hidden in the housing and is protected there against unintentional intervention. Through an additional lever, the SPEED works like a back pull runner when climbing.

The runner remains short and thus also the catch path. This provides climbing comfort and reduces fall-related injuries. In the event of a back pull failure, the runner can only reach a fixed preset maximum speed. If he exceeds this, the independently acting second safety device engages: a centrifugal brake swings out the catch bar and the runner blocks.

The follower safety gear is compatible with C-profile rails of the SKYTAC rail from SKYLOTEC or the SÖLL GlideLoc rail, which allows a variety of uses. Solid aluminum housing, stainless steel axles and metal guide rollers ensure low wear and tear.

- Uncompromising safety due to two redundant catch systems.
 - Reduction of misapplications due to interlocking
 - Comfortable and fatigue-free climbing thanks to double guide rollers.
 - Various use due to compatibility with SKYTAC and SÖLL GlideLoc rail.
- Further information:

https://www.skylotec.com/eu_de/permanente-absturzsicherung/produkte/vertikale-systeme/#skytac

<https://www.skylotec.com/eu_de/permanent
e-

FEATURES

Colour:	Grey
Max. number of persons:	1
Maximum load:	150.00 kg
Rope access technique:	No
Vertical systems:	Vertical rail system

DIMENSIONS

Rail length:	0.00 m
Rail width:	0.06 m

MATERIAL

Material:	Aluminium, Steel
-----------	------------------

DATASHEET

SPEED

absturzsicherung/produkte/vertikale-
systeme/#skytac>